

# AS 504

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	83 A8
<b>LI/SS FREE ROLLING</b>	95 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94019267	<b>RC (IN)</b>	78.8
<b>SW (IN)</b>	7.4	<b>RIM REC</b>	4.5
<b>OD (IN)</b>	26.9	<b>PR</b>	6
<b>SLR (IN)</b>	11.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	36
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520
5 DW	1500
15 DW	1270
20 DW	1200
25 DW	1070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.