

## TR 135

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>12.4 - 24</b>  |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> |                   |
| <b>MACHINERY</b>    | TRACTOR / TRAILER |
| <b>VERSION</b>      | STANDARD          |
| <b>TL/TT</b>        | TT                |
| <b>LI/SS</b>        | 128 A6            |



### DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 315  | <b>RIM REC</b> | W 11           |
| <b>OD (MM)</b>  | 1160 | <b>RIM ALT</b> | W 9 ; W 10     |
| <b>SLR (MM)</b> | 543  | <b>ECE</b>     | E4-106R-002040 |
| <b>RC (MM)</b>  | 3573 | <b>PR</b>      | 12             |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.50</b> |
| 30                | 1800        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.