


AGRIMAX FORCE



TIRE SIZE	IF 480/95 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	170 D

DIMENSÕES US STANDARD

CÓDIGO USA	94058006	RC (IN)	258.8
SW (IN)	18.9	RIM REC	DW 16 B
OD (IN)	85.4	ECE	E11-106R-004898
SLR (IN)	39.4	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5650	6490	7460	8420	9380	10350	11310	12040
FROM 40 TO 25	6220	7140	8200	9260	10320	11380	12430	13200
20	6460	7420	8520	9620	10720	11830	12930	13760
12	6710	7700	8850	10000	11130	12280	13430	14290
5	7890	9060	10410	11750	13090	14440	15780	16800
*UPTO 5 CYC WITH FRONT LOADER	8700	10000	11470	12960	14440	15920	17400	18520
5HT	6460	7420	8520	9620	10720	11830	12930	13760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.