

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	MAQUINARIA AGRÍCOLA / REMOLQUE / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	154 A8/150 B
<b>LI/SS FREE ROLLING</b>	167 A8/163 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	550	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1260	<b>ECE</b>	E11-106R-004397
<b>SLR (MM)</b>	547	<b>PR</b>	16
<b>RC (MM)</b>	3640		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40	2.60	2.80
10 FR	6970	7310	7630
20 FR	6275	6575	6865
30 FR	5580	5845	6105
40 FR	4980	5220	5450
50 FR	4480	4700	4875
10 DW	4795	5025	5250
20 DW	4315	4525	4725
30 DW	3835	4020	4200
40 DW	3425	3590	3750
50 DW	3085	3230	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.