


# EARTHMAX SR 49 M

**29.5 R 25**

|                     |  |
|---------------------|--|
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / YÜK TAŞIMA DAMPERİ (LHD) /<br>YÜKLEYİCİ / DÜŞÜK PROFILLI<br>DAMPERLI KAMYON      |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 216 A2   |



## UNDEFINED IS STANDARD

|                 |           |                    |    |
|-----------------|-----------|--------------------|----|
| <b>OD (MM)</b>  | 1905      | <b>TRA CODE</b>    | L4 |
| <b>SLR (MM)</b> | 844       | <b>STAR RATING</b> | ★★ |
| <b>RC (MM)</b>  | 5600      |                    |    |
| <b>RIM REC</b>  | 25.00/3.5 |                    |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 19000 | 19500 | 20000 | 20600 | 21200 | 22400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.