


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/60 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D



DIMENSIONS US STANDARD

CODE USA	94001222	RC (IN)	196.7
SW (IN)	26.0	RIM REC	DW 23 B
OD (IN)	66.0	RIM ALT	DW21B
SLR (IN)	29.5	ECE	E11-106R-007210

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5740	6640	7540	8550	9340	10120	11240
FROM 40 TO 25	6300	7290	8280	9390	10250	11110	12350
20	6430	7440	8440	9580	10460	11340	12600
12	6560	7580	8610	9770	10660	11560	12840
5	6930	8010	9100	10330	11280	12220	13580
*UPTO 5 CYC WITH FRONT LOADER	8820	10210	11580	13140	14350	15560	17280
5 HT	6430	7440	8440	9580	10460	11340	12600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.