

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>260/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	109 A8 ; 109 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94067909	<b>RC (IN)</b>	90.0
<b>SW (IN)</b>	10.2	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	30.3	<b>RIM ALT</b>	W 8 L; W 9
<b>SLR (IN)</b>	13.7	<b>ECE</b>	E11-106R-007158

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1070	1240	1420	1600	1780	1970	2140	2280
<b>25</b>	1070	1240	1420	1600	1780	1970	2140	2280
<b>20</b>	1150	1330	1530	1710	1910	2110	2300	2440
<b>5 LT</b>	1450	1660	1900	2140	2400	2640	2880	3060
<b>5 HT</b>	1150	1330	1530	1710	1910	2110	2300	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.