

AGRIMAX RT 955

| | |
|---------------------|---|
| TIRE SIZE | 210/95 R 28 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 116 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94042548 | RC (IN) | 132.4 |
| SW (IN) | 8.4 | RIM REC | W 7 |
| OD (IN) | 43.7 | RIM ALT | W 6 |
| SLR (IN) | 20.2 | ECE | E4-106R-001819 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 |
|-----------|------|------|------|------|------|------|------|------|------|
| 30 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 | - |
| 25 | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 | - |
| 20 | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 | - |
| 5 | 1910 | 2190 | 2450 | 2690 | 2980 | 3270 | 3800 | 4010 | 4130 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.