


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8 ; 155 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94070299	<b>RC (IN)</b>	191.7
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	63.2	<b>RIM ALT</b>	W 16 L; W 14 L
<b>SLR (IN)</b>	28.9	<b>ECE</b>	E11-106R-007532

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	3340	3940	4530	5050	5640	6150	6760	7440	8040	8540
25	3340	3940	4530	5050	5640	6150	6760	7440	8040	8540
20	3570	4210	4850	5400	6040	6590	7230	7970	8610	9150
5 LT	4480	5270	6070	6770	7560	8260	9050	9960	10770	11450
5 HT	3570	4210	4850	5400	6040	6590	7230	7970	8610	9150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.