

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 320/85 R 36 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 128 A8/B |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94021628 | RC (IN) | 173.4 |
| SW (IN) | 13.0 | RIM REC | W 11 |
| OD (IN) | 57.4 | RIM ALT | W 9; W 10 |
| SLR (IN) | 26.5 | ECE | E4-106R-000762 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|------|
| 30 | 2180 | 2550 | 2900 | 3260 | 3620 | 3970 |
| 25 | 2180 | 2550 | 2900 | 3260 | 3620 | 3970 |
| 20 | 2350 | 2730 | 3110 | 3490 | 3880 | 4250 |
| 5 LT | 2930 | 3420 | 3890 | 4380 | 4850 | 5320 |
| 5 HT | 2350 | 2730 | 3110 | 3490 | 3880 | 4250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.