

AGRIMAX V-FLECTO

TIRE SIZE	VF 520/85 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	177 D



DIMENSIONER US STANDARD

USA CODE	94517008	RC (IN)	255.6
SW (IN)	21.1	RIM REC	DW 18 L
OD (IN)	85.0	RIM ALT	DW 16 L
SLR (IN)	38.3	ECE	E11-106R-0011305

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6880	7900	9070	10240	11410	12590	13760	14640
FROM 40 TO 25	7560	8690	9980	11260	12540	13830	15120	16090
20	7700	8860	10170	11490	12800	14110	15420	16410
12	7860	9030	10370	11710	13050	14380	15720	16730
5	8310	9560	10970	12390	13800	15220	16630	17700
*UPTO 5 CYC WITH FRONT LOADER	10590	12170	13980	15770	17580	19380	21190	22530
5HT	7700	8860	10170	11490	12800	14110	15420	16410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.