

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	200/65 R 16
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTAT PODGORII / RECOLTAREA LIVEZILOR / TRACTOR MIC / TRACTOR / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	94 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94070640	<b>RC (IN)</b>	78.7
<b>SW (IN)</b>	8.0	<b>RIM REC</b>	W6
<b>OD (IN)</b>	26.2	<b>ECE</b>	E11-106R-007678
<b>SLR (IN)</b>	12.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	700	820	940	1040	1150	1240	1380	1480
25	700	820	940	1040	1150	1240	1380	1480
20	750	890	1010	1120	1230	1330	1480	1590
5 LT	940	1100	1260	1390	1540	1660	1860	1990
5 HT	750	890	1010	1120	1230	1330	1480	1590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.