


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 600/70 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94044689	<b>RC (IN)</b>	183.2
<b>SW (IN)</b>	23.7	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	61.1	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	27.3	<b>ECE</b>	E4-106R-000795

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4710	5410	6220	7020	7810	8620	9420	10030
<b>FROM 40 TO 25</b>	5180	5950	6830	7720	8600	9480	10360	11000
20	5380	6180	7100	8020	8940	9850	10770	11460
12	5590	6430	7370	8330	9280	10230	11190	11900
5	6570	7550	8670	9800	10910	12040	13150	14000
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7250	8330	9570	10800	12040	13270	14510	15430
5 HT	5380	6180	7100	8020	8940	9850	10770	11460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.