

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	145 A8/141 B
LI/SS FREE ROLLING	157 A8/154 B



DIMENSIONS IS STANDARD

SW (MM)	510	RIM REC	16.00
OD (MM)	945	ECE	E4-106R-002305
SLR (MM)	416	PR	18
RC (MM)	2750		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80	3.90	4.00
10 FR	5605	5690	5775
20 FR	5045	5120	5200
30 FR	4485	4555	4620
40 FR	4005	4065	4125
50 FR	3605	3660	3750
10 DW	3940	3995	4060
20 DW	3545	3595	3655
30 DW	3155	3200	3250
40 DW	2815	2855	2900
50 DW	2535	2570	2575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.