


# AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 54
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	168 D



## DIMENSIONES US STANDARD

CÓDIGO USA	94075249	RC (IN)	234.1
SW (IN)	12.7	RIM REC	W 11
OD (IN)	76.7	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (IN)	35.8	ECE	E11-106R-009070

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	4920	5490	6180	6750	7090	7430	7670	7890	8290	8690	9030	9370	9660	9950	10230	10520	10970	11420
FROM 40 TO 25	5320	5940	6670	7290	7670	8030	8280	8530	8960	9400	9760	10130	10440	10750	11060	11370	11870	12350
20	5430	6060	6820	7450	7820	8190	8450	8700	9140	9580	9960	10340	10650	10970	11280	11600	12110	12600
12	5530	6180	6950	7590	7970	8360	8610	8870	9320	9770	10160	10540	10860	11180	11500	11820	12340	12850
5	5850	6530	7350	8020	8430	8830	9110	9390	9860	10330	10740	11150	11490	11820	12160	12500	13040	13580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.