

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>360/70 R 24</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | STANDARD                                                                        |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 122 D                                                                           |

## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94063017 | <b>RC (IN)</b> | 133.7           |
| <b>SW (IN)</b>    | 14.1     | <b>RIM REC</b> | W 11            |
| <b>OD (IN)</b>    | 45.4     | <b>RIM ALT</b> | W 10 ; W 12     |
| <b>SLR (IN)</b>   | 20.4     | <b>ECE</b>     | E11-106R-005824 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>40</b>   | 1820 | 2120 | 2410 | 2710 | 3010 | 3310 |
| <b>30</b>   | 1920 | 2230 | 2540 | 2850 | 3160 | 3470 |
| <b>25</b>   | 2000 | 2330 | 2660 | 2980 | 3310 | 3630 |
| <b>20</b>   | 2090 | 2440 | 2780 | 3120 | 3460 | 3800 |
| <b>5 LT</b> | 2450 | 2840 | 3240 | 3640 | 4030 | 4430 |
| <b>5 HT</b> | 2090 | 2440 | 2780 | 3120 | 3460 | 3800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

