

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>270/95 R 54</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94032839	<b>RC (IN)</b>	228.9
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	74.2	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (IN)</b>	35.2	<b>ECE</b>	E4-106R-001410

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	2580	3370	4100	4500	4760	5220	5690	6150	6600	-
25	2580	3370	4100	4500	4760	5220	5690	6150	6600	-
20	2770	3620	4400	4820	5100	5600	6100	6590	7080	-
5	3080	3870	4760	5650	6550	6750	7540	8330	9130	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.