


AGRIMAX RT 765M



TIRE SIZE	710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	173 D ; 176 A8

DIMENSIONS IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	2061	RIM ALT	DW 25 B
SLR (MM)	922	ECE	E11-106R-006018
RC (MM)	6174	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3055	3510	4030	4550	5070	5590	6110	6500
50	3210	3690	4235	4780	5325	5870	6420	6825
40	3350	3845	4415	4985	5555	6125	6695	7120
30	3515	4040	4635	5235	5835	6430	7030	7475
10 LT	4095	4705	5405	6100	6795	7495	8190	8710
10 HT	3515	4040	4635	5235	5835	6430	7030	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.