


# EARTHMAX SR 23

<b>TIRE SIZE</b>	<b>15.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTONIVELADORA / PALA CARGADORA
<b>VERSIÓN</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 A8 ; 169 A2



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94046829	<b>RIM REC</b>	12.00/1.3
<b>OD (IN)</b>	49.8	<b>TRA CODE</b>	G2/L2
<b>SLR (IN)</b>	22.0	<b>STAR RATING</b>	★
<b>RC (IN)</b>	147.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73
25	3420	3860	4400	4800	5200	5680	6150	6600	-	-	-	-	-
5	-	-	-	-	-	-	-	-	11000	11400	12000	12300	12800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.