


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>750/65 R 26 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOISSONNEUSE / MACHINE À RÉCOLTER LE COTON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	764	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1636	<b>RIM ALT</b>	DW 23 B
<b>SLR (MM)</b>	713	<b>ECE</b>	E4-106R-001496
<b>RC (MM)</b>	4908	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2915	3340	4085	4400	4930	5300	5720	6150
40	2915	3340	4085	4400	4930	5300	5720	6150
30	3125	3580	4370	4715	5280	5675	6125	6585
15 CYC	4810	5510	6735	7260	8135	8745	9440	10150
10 CYC	5250	6015	7350	7920	8875	9540	10300	11070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.