


# AGRIMAX SPARGO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 320/90 R 54</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 168 D  |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                            |
|-----------------|------|----------------|----------------------------|
| <b>SW (MM)</b>  | 323  | <b>RIM REC</b> | W 11                       |
| <b>OD (MM)</b>  | 1948 | <b>RIM ALT</b> | W 10; DW 10; W 10 L; DW 11 |
| <b>SLR (MM)</b> | 910  | <b>ECE</b>     | E11-106R-009070            |
| <b>RC (MM)</b>  | 5946 | <b>SRI</b>     | 925                        |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 1.0  | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6  | 3.8  | 4.0  | 4.2  | 4.4  |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70            | 2230 | 2490 | 2800 | 3060 | 3215 | 3370 | 3475 | 3575 | 3760 | 3940 | 4095 | 4250 | 4380 | 4510 | 4640 | 4770 | 4975 | 5180 |
| FROM 65 TO 40 | 2410 | 2690 | 3025 | 3305 | 3475 | 3640 | 3755 | 3865 | 4060 | 4260 | 4425 | 4595 | 4735 | 4875 | 5015 | 5155 | 5380 | 5600 |
| 30            | 2460 | 2745 | 3090 | 3375 | 3545 | 3715 | 3830 | 3945 | 4145 | 4345 | 4515 | 4690 | 4830 | 4975 | 5115 | 5260 | 5490 | 5715 |
| 20            | 2505 | 2800 | 3150 | 3440 | 3615 | 3790 | 3905 | 4020 | 4225 | 4430 | 4605 | 4780 | 4925 | 5070 | 5215 | 5360 | 5595 | 5825 |
| 10            | 2650 | 2960 | 3330 | 3635 | 3820 | 4005 | 4130 | 4255 | 4470 | 4685 | 4870 | 5055 | 5210 | 5360 | 5515 | 5670 | 5915 | 6160 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.