

# AGRIMAX RT 765

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>580/70 R 38</b>                                                    |
| <b>UM</b>        | IS STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STEEL BELTED                                                          |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 180 D                                                                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 577  | <b>RIM REC</b> | W 18 L            |
| <b>OD (MM)</b>  | 1827 | <b>RIM ALT</b> | DW 18 L ; DD 18 L |
| <b>SLR (MM)</b> | 821  | <b>ECE</b>     | E11-106R-005836   |
| <b>RC (MM)</b>  | 5505 | <b>SRI</b>     | 875               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  | 4.6  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65         | 3180 | 3875 | 4930 | 5480 | 6000 | 6470 | 6930 | 7370 | 7790 | 8000 |
| 50         | 3340 | 4070 | 5180 | 5755 | 6300 | 6795 | 7280 | 7740 | 8180 | 8400 |
| 40         | 3485 | 4245 | 5400 | 6005 | 6570 | 7085 | 7590 | 8075 | 8535 | 8760 |
| 30         | 3660 | 4460 | 5670 | 6305 | 6900 | 7445 | 7970 | 8480 | 8960 | 9200 |
| 25         | 3770 | 4595 | 5845 | 6495 | 7110 | 7670 | 8215 | 8735 | 9235 | 9480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.