

# AW 711

<b>TIRE SIZE</b>	<b>15 R 19.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 D



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94044931	<b>RC (IN)</b>	121.8
<b>SW (IN)</b>	15.3	<b>RIM REC</b>	11.75
<b>OD (IN)</b>	40.1	<b>RIM ALT</b>	12.75
<b>SLR (IN)</b>	18.5	<b>ECE</b>	E11-106R-006649

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73	80
40	1450	1880	2300	2580	3010	3380	3760	4080	4510	5040	5360
30	1850	2400	2950	3290	3850	4320	4800	5210	5760	6450	6850
25	1950	2520	3100	3450	4030	4530	5040	5470	6040	6760	7190
15	2120	2740	3370	3770	4400	4940	5490	5960	6590	7370	7840
5	2940	3810	4680	5220	6090	6850	7610	8280	9150	10230	10880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.