


EARTHMAX SR 45

| | |
|---------------------|--|
| TIRE SIZE | 18.00 R 33 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ |
| VERSION | STANDARD COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 191 B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|-----------|--------------------|----|
| OD (MM) | 1870 | TRA CODE | E4 |
| SLR (MM) | 856 | STAR RATING | ★★ |
| RC (MM) | 5608 | | |
| RIM REC | 13.00/2.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|------|------|------|------|------|-------|-------|-------|-------|
| 50 | 8500 | 8750 | 9000 | 9250 | 9750 | 10000 | 10300 | 10600 | 10900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.