


AW 726

| | |
|---------------------------|--|
| TIRE SIZE | 420/55 - 17 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 121 A8 |
| LI/SS FREE ROLLING | 133 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94055647 | RC (IN) | 101.7 |
| SW (IN) | 16.3 | RIM REC | 13.00 |
| OD (IN) | 35.0 | ECE | E11-106R-005265 |
| SLR (IN) | 15.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 29 |
|-----------|------|
| 5 FR | 6360 |
| 15 FR | 5400 |
| 20 FR | 5080 |
| 25 FR | 4540 |
| 5 DW | 4480 |
| 15 DW | 3800 |
| 20 DW | 3580 |
| 25 DW | 3200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.