


# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>15.5/80 - 24</b>   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS            |
| <b>MACHINERY</b>          | SOLLEVATORE TELESOPICO /<br>RIMORCHIO DA CAMPO / ATTREZZI<br>AGRICOLI / SOLLEVATORE<br>TELESOPICO |
| <b>VERSIONE</b>           | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 145 A8  |
| <b>LI/SS FREE ROLLING</b> | 157 A8  |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94018963 | <b>RC (IN)</b> | 152.6           |
| <b>SW (IN)</b>    | 15.1     | <b>RIM REC</b> | W 12            |
| <b>OD (IN)</b>    | 49.7     | <b>RIM ALT</b> | W 13; W 14 L    |
| <b>SLR (IN)</b>   | 22.4     | <b>ECE</b>     | E11-106R-003574 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44    |
|-----------|-------|
| 5 FR      | 12730 |
| 15 FR     | 10820 |
| 20 FR     | 10180 |
| 25 FR     | 9090  |
| 5 DW      | 8950  |
| 15 DW     | 7610  |
| 20 DW     | 7160  |
| 25 DW     | 6390  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.