

# AW 712

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>260/70 R 15.3</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINI DE IMPLEMENTARE /<br>PULVERIZATOR / MAȘINI DE<br>IMPLEMENTARE                     |
| <b>VERSION</b>      | IMPLEMENT  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 134 A8/B   |



## DIMENSIUNI US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94059584 | <b>RC (IN)</b> | 90.7             |
| <b>SW (IN)</b>  | 10.4     | <b>RIM REC</b> | 9.00             |
| <b>OD (IN)</b>  | 29.9     | <b>ECE</b>     | 'E11-106R-005096 |
| <b>SLR (IN)</b> | 13.5     |                |                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 58   | 73   |
|-----------|------|------|------|------|------|------|------|------|------|------|------|
| 30        | 1360 | 1730 | 2110 | 2440 | 2810 | 3190 | 3420 | 3790 | 3920 | 4400 | 4670 |
| 25        | 1360 | 1730 | 2110 | 2440 | 2810 | 3190 | 3420 | 3790 | 3920 | 4400 | 4670 |
| 20        | 1520 | 1940 | 2360 | 2720 | 3140 | 3560 | 3820 | 4240 | 4390 | 4930 | 5240 |
| 15        | 1620 | 2060 | 2510 | 2900 | 3340 | 3790 | 4070 | 4520 | 4660 | 5240 | 5570 |
| 10        | 1720 | 2180 | 2660 | 3080 | 3540 | 4010 | 4310 | 4780 | 4940 | 5540 | 5900 |
| 5         | 1910 | 2420 | 2950 | 3410 | 3940 | 4450 | 4780 | 5310 | 5490 | 6160 | 6550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.