

# PL 801

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 7.50 - 15   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ERNTemaschine /<br>Landwirtschaftliche Geräte /<br>Rotorschwader / Gabelstapler /<br>Erntemaschine / Gabelstapler |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## ABMESSUNGEN IS STANDARD

|                 |     |                |              |
|-----------------|-----|----------------|--------------|
| <b>SW (MM)</b>  | 220 | <b>RIM REC</b> | 6.0          |
| <b>OD (MM)</b>  | 814 | <b>RIM ALT</b> | 6.00 S ; 6.5 |
| <b>SLR (MM)</b> | 0   | <b>PR</b>      | 14           |
| <b>RC (MM)</b>  | 0   |                |              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR         | 9.20 | 9.70 |
|--------------------|------|------|
| 25 LOAD WHEEL      | 3430 | -    |
| 25 STEER WHEEL     | 2900 | -    |
| 10 OTHER VEHICLES  | 2900 | -    |
| 25 OTHER VEHICLES  | 2130 | -    |
| STATIC SIDE LOADER | -    | 4685 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.