

# AGRIMAX RT 765

|              |                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------|
| TIRE SIZE    | 620/70 R 42                                                                                        |
| UM           | US STANDARD                                                                                        |
| CONSTRUCTION |  RADIAL           |
| MACHINERY    | FELDSPRITZE / TRACTOR /<br>TRAUBENERNTEMASCHINE /<br>ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION      | STANDARD                                                                                           |
| TIRE TYPE    | TL                                                                                                 |
| LI/SS        | 173 D                                                                                              |



## ABMESSUNGEN US STANDARD

|          |          |         |                 |
|----------|----------|---------|-----------------|
| USA-CODE | 94063093 | RC (IN) | 228.5           |
| SW (IN)  | 24.6     | RIM REC | DW 20 B         |
| OD (IN)  | 76.2     | RIM ALT | DW 18 L         |
| SLR (IN) | 34.5     | ECE     | E11-106R-005833 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15    | 17    | 20    | 23    | 29    | 35    | 41    | 47    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | 5590 | 6590 | 7590  | 8450  | 9460  | 10320 | 11320 | 12180 | 13330 | 14330 |
| 30        | 5870 | 6920 | 7980  | 8880  | 9930  | 10840 | 11890 | 12800 | 14000 | 15050 |
| 25        | 6130 | 7230 | 8320  | 9270  | 10360 | 11310 | 12400 | 13350 | 14600 | 15700 |
| 20        | 6440 | 7580 | 8740  | 9730  | 10880 | 11870 | 13030 | 14010 | 15330 | 16480 |
| 5 LT      | 7500 | 8840 | 10180 | 11330 | 12680 | 13830 | 15180 | 16320 | 17870 | 19200 |
| 5 HT      | 6440 | 7580 | 8740  | 9730  | 10880 | 11870 | 13030 | 14010 | 15330 | 16480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.