

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 700/50 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊗ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | HIGH SPEED |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 158 B/154 E |
| LI/SS FREE ROLLING | 170 B/166 E |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 700 | RIM REC | 24.00 |
| OD (MM) | 1270 | ECE | E11-106R-004555 |
| SLR (MM) | 550 | PR | 16 |
| RC (MM) | 3775 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.00 | 2.20 | 2.40 |
|------------|------|------|------|
| 10 FR | 8430 | 8910 | 9380 |
| 20 FR | 7585 | 8020 | 8440 |
| 30 FR | 6740 | 7130 | 7505 |
| 40 FR | 6020 | 6365 | 6700 |
| 50 FR | 5420 | 5730 | 6000 |
| 70 FR | 4755 | 5030 | 5300 |
| 10 DW | 5980 | 6320 | 6650 |
| 20 DW | 5380 | 5690 | 5985 |
| 30 DW | 4780 | 5055 | 5320 |
| 40 DW | 4270 | 4515 | 4750 |
| 50 DW | 3845 | 4065 | 4250 |
| 70 DW | 3375 | 3565 | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.