

AGRIMAX V-FLECTO

TIRE SIZE	VF 800/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	187 D



DIMENSIONES US STANDARD

CÓDIGO USA	94073979	RC (IN)	242.3
SW (IN)	31.7	RIM REC	DW 28 B
OD (IN)	82.1	RIM ALT	DW25 B; DW27B; DW30B
SLR (IN)	35.0	ECE	E11-106R-007205

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9790	11350	12920	14680	16250	17810	19560
FROM 40 TO 25	10750	12470	14190	16130	17850	19560	21490
20	10970	12720	14470	16450	18200	19950	21920
12	11180	12970	14760	16770	18560	20350	22350
5	11830	13720	15610	17740	19630	21520	23640
UPTO 20 CYC	12200	14150	16100	18310	20260	22210	24400
UPTO 10 CYC	14570	16900	19220	21850	24180	26510	29130
UPTO 5 CYC	15960	18520	21080	23940	26500	29060	31920
5 HT	10970	12720	14470	16450	18200	19950	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.