

# AW 705

<b>TIRE SIZE</b>	14.0/65 - 16
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	142 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	353	<b>RIM REC</b>	11.0
<b>OD (MM)</b>	870	<b>ECE</b>	E4-106R-001901
<b>SLR (MM)</b>	388	<b>PR</b>	14
<b>RC (MM)</b>	2549		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.