


# AGRIMAX SPARGO

<b>TYRE SIZE</b>	<b>VF 420/95 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	177 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	419	<b>RIM REC</b>	DW 14
<b>OD (MM)</b>	2068	<b>RIM ALT</b>	DW 13; W 13; W 14
<b>SLR (MM)</b>	943	<b>ECE</b>	E4-106R-002651
<b>RC (MM)</b>	6210	<b>SRI</b>	975

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
70	3715	4115	4515	4710	4980	5110	5245	5510	5775	5975	6240	6440	6640
<b>FROM 65 TO 40</b>	4085	4525	4960	5180	5475	5620	5765	6055	6350	6570	6860	7080	7300
30	4165	4615	5060	5285	5580	5730	5880	6175	6475	6700	6995	7220	7445
20	4250	4705	5160	5385	5690	5840	5995	6295	6600	6830	7130	7360	7590
10	4495	4975	5460	5700	6020	6180	6340	6660	6985	7225	7545	7785	8030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.