

AGRIMAX RT 765

TIRE SIZE	480/70 R 38
UM	IS STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	145 D



ABMESSUNGEN IS STANDARD

SW (MM)	479	ECE	E11-106R-005832
OD (MM)	1681	SRI	800
SLR (MM)	764	TRA CODE	R1W
RC (MM)	5055	TREAD DEPTH (MM)	49,5
RIM REC	W 15 L	TKPH (TK/H)	0
RIM ALT	W 14 L ; W 16 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1595	1860	2120	2380	2640	2900
50	1675	1950	2225	2500	2775	3045
40	1750	2040	2325	2610	2895	3180
30	1835	2135	2435	2735	3035	3335
10 LT	2140	2490	2840	3190	3540	3890
10 HT	1935	2135	2435	2735	3035	3335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.