

AGRIMAX RT 955

TIRE SIZE	340/85 R 48
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	151 D ; 154 A8



DIMENSÕES US STANDARD

CÓDIGO USA	94059287	RC (IN)	219.4
SW (IN)	13.9	RIM REC	W 12
OD (IN)	70.7	RIM ALT	W 11
SLR (IN)	33.7	ECE	E11-106R-005765

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	20	23	29	35	41	46	52	58	64
40	3270	3660	4110	4500	4950	5260	5790	6240	6620	7000	7610
30	3440	3840	4320	4720	5200	5520	6070	6560	6960	7350	7990
25	3560	3970	4460	4880	5380	5710	6280	6780	7200	7610	8270
20	3770	4210	4730	5170	5700	6040	6660	7190	7620	8060	870
5	4920	5480	6160	6730	7420	7880	8670	9360	9930	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.