


# AGRIMAX FORTIS



<b>TIRE SIZE</b>	<b>710/75 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D ; 172 E

## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94050123	<b>RC (IN)</b>	252.2
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	84.0	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	38.2	<b>ECE</b>	E4-106R-001835

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6670	7780	8750	9720	10700	11530	12790	13890
40	7310	8520	9590	10650	11720	12630	14000	15210
30	7670	8950	10060	11190	12300	13260	14700	15970
25	8000	9340	10500	11670	12840	13830	15340	16670
20	8400	9800	11020	12250	13470	14530	16100	17490
5 LT	9790	11420	12850	14270	15710	16930	18760	20390
5 HT	8400	9800	11020	12250	13470	14530	16100	17490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.