DATA SHEET

PRINTED ON
22-04-2026

AGRIMAX RT 765

TYRE SIZE	**650/75 R 42**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	170 D

DIMENSIONS IS STANDARD

SW (MM)	655	**RIM REC**	DW21B
OD (MM)	2043	**RIM ALT**	DW20B;DW23B
SLR (MM)	916	**ECE**	E11-106R-006402
RC (MM)	6147	**SRI**	975

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2820	3240	3720	4200	4680	5160	5640	6000
50	2965	3405	3910	4410	4915	5420	5925	6300
40	3090	3550	4075	4600	5125	5655	6180	6570
30	3245	3730	4280	4830	5385	5935	6490	6900
10 LT	3780	4345	4985	5630	6275	6915	7560	8040
10 HT	3245	3730	4280	4830	5385	5935	6490	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..