

# AW 711

<b>TIRE SIZE</b>	<b>VF 480/45 R 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	491	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	866	<b>ECE</b>	E4-106R-002652
<b>SLR (MM)</b>	363	<b>SRI</b>	410
<b>RC (MM)</b>	2644		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
<b>FROM 10 TO 50 KM/H</b>	1585	2020	2455	2780	3220	3655	4035	4415	4855	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.