

# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94060115	<b>RC (IN)</b>	100.0
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E11-106R-007157
<b>SLR (IN)</b>	15.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	59
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810
5 DW	4780
15 DW	4070
20 DW	3820
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.