

# FLOTATION 558

<b>TYRE SIZE</b>	<b>500/45 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	136 A8/132 B
<b>LI/SS FREE ROLLING</b>	148 A8/144 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006267	<b>RC (IN)</b>	124.7
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	41.1	<b>ECE</b>	E4-106R-002307
<b>SLR (IN)</b>	18.5	<b>PR</b>	12

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	33	36	39
5 FR	8860	9290	9720
10 FR	7970	8370	8750
20 FR	7090	7430	7780
25 FR	6330	6640	6940
30 FR	5700	5970	6170
5 DW	6290	6600	6910
10 DW	5670	5940	6220
20 DW	5040	5280	5530
25 DW	4500	4720	4940
30 DW	4050	4240	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.