


RIDEMAX FROST

| | |
|---------------------|--|
| TIRE SIZE | 540/80 R 38 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 172 A8 ; 167 D |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94076604 | RC (IN) | 220.1 |
| SW (IN) | 21.7 | RIM REC | DW 18 L |
| OD (IN) | 72.2 | RIM ALT | DW 16 L |
| SLR (IN) | 33.1 | ECE | E11-106R-0010575 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 38 | 41 | 44 | 46 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5290 | 6980 | 8410 | 9260 | 9850 | 10340 | 10810 | 11420 | 12010 |
| 30 | 5720 | 7540 | 9090 | 10010 | 10650 | 11180 | 11690 | 12350 | 12980 |
| 25 | 6120 | 8060 | 9720 | 10700 | 11400 | 11950 | 12500 | 13190 | 13890 |
| 20 | 6350 | 8370 | 10100 | 11110 | 11830 | 12400 | 12980 | 13700 | 14420 |
| 10 | 6670 | 8780 | 10600 | 11660 | 12420 | 13030 | 13630 | 14400 | 15140 |
| 5 | 7620 | 10040 | 12110 | 13330 | 14200 | 14890 | 15570 | 16450 | 17310 |
| 3 | 8840 | 11650 | 14050 | 15460 | 16470 | 17270 | 18070 | 19070 | 20070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.