

AGRIMAX RT 657

TIRE SIZE	420/65 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	135 D ; 138 A8



РАЗМЕРЫ US STANDARD

USA CODE	94041862	RC (IN)	124.5
SW (IN)	16.5	RIM REC	W 13
OD (IN)	41.5	RIM ALT	W 11 ; W 12
SLR (IN)	18.4	ECE	E4-106R-001390

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2260	2650	3030	3370	3700	3990	4430	4800
30	2380	2780	3190	3540	3890	4200	4650	5050
25	2450	2870	3280	3650	4010	4320	4790	5200
20	2600	3050	3490	3880	4270	4600	5090	5530
5 LT	3030	3550	4070	4520	4970	5360	5940	6450
5 HT	2600	3050	3490	3880	4270	4600	5090	5530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.