

EARTHMAX SR 49 M



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 49 M



EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	26.5 R 25	TL	SH4	****	-	22.00/3.0	-	0	708	1782	801	5297	56	CR
	29.5 R 25	TL	E4/L4	**	200 B 216 A2	25.00/3.5	-	220	780	1905	844	5600	57	CR
	29.5 R 25	TL	E4/L4	****/***	-	25.00/3.5	-	0	780	1905	844	5600	57	CR
	29.5 R 25	TL	L4	**	216 A2	25.00/3.5	-	0	780	1905	844	5600	57	CR
	26.5 R 25	TL	E4/L4	**/*	193 B 202 A2	22.00/3.0	-	165	708	1782	801	5297	56	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
B	223 kg		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
29.5 R 25	TL	E4/L4	**/*	200 B 208 A2	25.00/3.5	-	220	780	1905	844	5600	57	CR
29.5 R 25	TL	SH4	****	-	25.00/3.5	-	0	780	1905	844	5600	57	CR
26.5 R 25	TL	E4/L4	****/**	-	22.00/3.0	-	0	708	1782	801	5297	56	CR
29.5 R 25	TL	L4	*	208 A2	25.00/3.5	-	0	780	1905	844	5600	57	CR
26.5 R 25	TL	L4	*	202 A2	22.00/3.0	-	0	708	1782	801	5297	56	CR
26.5 R 25	TL	L4	**	209 A2	22.00/3.0	-	0	708	1782	801	5297	56	CR
29.5 R 29	TL	SH4	****	-	25.00/3.5	24.00/3.5 26.00/3.5	0	786	2006	906	6320	60	CR
29.5 R 29	TL	L4	***	223 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	786	2006	906	6320	60	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
E4/L4/SH4		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	
B		223 kg	