

EM 937 E3 (L)



EM 937 E3 (L)



EM 937 (E-3/L-3) has been specially designed for loaders and backhoe loaders in dig and load applications, depending on the size. It features excellent durability and provides cut and chip resistance.



SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION	
				REC RIM	ALT RIM						
											
Ø24"	14.00 - 24	TL	32	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
	14.00 - 24	TT	28	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
	14.00 - 24	TT	20	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
	14.00 - 24	TT	24	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
	14.00 - 24	TL	20	-	10.00 W	-	14.8	53.9	24.7	159.4	STD

SB: STEEL BELTED, STD: STANDARD, AR + SB: ARAMID + STEEL BELTED, AB: ARAMID BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION	
				REC RIM	ALT RIM						
											
14.00 - 24	TT	32	-	10.00 W	-	14.8	53.9	24.7	159.4	STD	
14.00 - 24	TL	28	-	10.00 W	-	14.8	53.9	24.7	159.4	STD	
14.00 - 24	TL	24	-	10.00 W	-	14.8	53.9	24.7	159.4	STD	
Ø25"	14.00 - 25	TT	20	-	10.00/1.5	-	14.8	53.9	24.4	161.6	SB
	14.00 - 25	TT	20	-	10.00/1.5	-	14.8	53.9	24.4	161.6	STD
	14.00 - 25	TT	20	-	10.00/1.5	-	14.8	53.9	24.4	161.6	AR + SB
	14.00 - 25	TT	24	-	10.00/1.5	-	14.8	53.9	24.4	161.6	STD
	14.00 - 25	TT	20	-	10.00/1.5	-	14.8	53.9	24.4	161.6	AB
	14.00 - 25	TT	12	-	10.00/1.5	-	15.4	53.9	24.4	161.6	STD
	14.00 - 25	TL	24	-	10.00/1.5	-	14.8	53.9	24.4	161.6	STD

SB: STEEL BELTED, STD: STANDARD, AR + SB: ARAMID + STEEL BELTED, AB: ARAMID BELTED

TECHNOLOGIES		PERFORMANCES	
	E3/L3		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index
-	-		

SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
14.00 - 25	TL	20	-	10.00/1.5	-	14.8	53.9	24.4	161.6	STD

SB: STEEL BELTED, STD: STANDARD, AR + SB: ARAMID + STEEL BELTED, AB: ARAMID BELTED

TECHNOLOGIES		PERFORMANCES	
	 E3/L3		
			
-	-	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	