

AGRIMAX RT 855

TIRE SIZE	250/85 R 22
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	113 A8/B



DIMENSIONS US STANDARD

CODE USA	94049332	RIM REC	W 8
SW (IN)	9.9	RIM ALT	W 7
OD (IN)	38.8	ECE	E11-106R-002973
SLR (IN)	17.8	TRA CODE	R1W
RC (IN)	116.7	TREAD DEPTH (32nd)	45.99

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.