


AGRIMAX FORCE

IF 420/85 R 38

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	155 D



UNDEFINED US STANDARD

USA CODE	94058044	RC (IN)	197.5
SW (IN)	16.5	RIM REC	DW 14 L
OD (IN)	65.7	RIM ALT	DW 15 L
SLR (IN)	30.7	ECE	E11-106R-004897

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	3650	4190	4810	5430	6050	6680	7300	7770
FROM 40 TO 25	4010	4610	5290	5970	6660	7340	8020	8550
20	4170	4780	5500	6210	6920	7630	8340	8880
12	4330	4970	5710	6450	7190	7930	8660	9230
5	5090	5840	6710	7580	8450	9310	10180	10850
*UPTO 5 CYC WITH FRONT LOADER	5610	6450	7410	8360	9310	10270	11230	11960
5 HT	4170	4780	5500	6210	6920	7630	8340	8880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.