


# AGRIMAX RT 855

	<b>520/85 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	165 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94057993	<b>RC (IN)</b>	254.8
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16L
<b>OD (IN)</b>	84.8	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	39.1	<b>ECE</b>	E11-106R-004895

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	5350	6140	7045	7950	8865	9770	10685	11355
25	5350	6140	7045	7950	8865	9770	10685	11355
20	5725	6570	7540	8525	9495	10465	11435	12160
5 LT	7165	8225	9450	10660	11885	13095	14320	15225
5 HT	5725	6570	7540	8525	9495	10465	11435	12160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.