DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX RT 765

TYRE SIZE	**520/70 R 34**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	SPECIAL
TYRE TYPE	TL
LI/SS	148 D

DIMENSIONS US STANDARD

USA CODE	94063192	**RC (IN)**	194.0
SW (IN)	20.3	**RIM REC**	W 16 L
OD (IN)	64.6	**RIM ALT**	W 15 L; W 18 L
SLR (IN)	29.1	**ECE**	E11-106R-005831

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	90	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..