


AGRIMAX FORCE

| | |
|--------------|--|
| TIRE SIZE | IF 650/75 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR |
| VERSÃO | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSÕES US STANDARD

| | | | |
|------------|----------|---------|-----------------|
| CÓDIGO USA | 94511242 | RC (IN) | 228.4 |
| SW (IN) | 25.6 | RIM REC | DW 23 B |
| OD (IN) | 76.4 | RIM ALT | DW 21 B |
| SLR (IN) | 34.1 | ECE | E11-106R-007385 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6520 | 7490 | 8590 | 9700 | 10810 | 11920 | 13020 | 13850 |
| FROM 40 TO 25 | 7160 | 8230 | 9440 | 10650 | 11880 | 13090 | 14310 | 15220 |
| 20 | 7450 | 8560 | 9830 | 11090 | 12360 | 13620 | 14890 | 15830 |
| 12 | 7730 | 8890 | 10200 | 11510 | 12820 | 14150 | 15460 | 16440 |
| 5 | 9090 | 10440 | 11990 | 13540 | 15080 | 16630 | 18170 | 19330 |
| UPTO 20 CYC | 9310 | 10690 | 12270 | 13850 | 15440 | 17010 | 18600 | 19780 |
| UPTO 10 CYC | 11090 | 12750 | 14630 | 16520 | 18400 | 20290 | 22170 | 23580 |
| UPTO 5 CYC | 12160 | 13970 | 16040 | 18110 | 20180 | 22250 | 24320 | 25860 |
| 5 HT | 7450 | 8560 | 9830 | 11090 | 12360 | 13620 | 14890 | 15830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.