

# AW 702

|                     |   |
|---------------------|---|
|                     | <b>10.5/65 - 16</b>   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | BALYA MAKINESI / UYGULAMALI<br>MAKINE / RÖMORK / BIÇERDÖVER /<br>UYGULAMALI MAKINE / RÖMORK |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |
|                     | 123 A8  |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94009220 | <b>RC (IN)</b> | 91.7            |
| <b>SW (IN)</b>  | 10.6     | <b>RIM REC</b> | W 9             |
| <b>OD (IN)</b>  | 29.9     | <b>RIM ALT</b> | W 8; W 8 L      |
| <b>SLR (IN)</b> | 13.8     | <b>ECE</b>     | E11-106R-003513 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 55   |
|-----------|------|
| 5 FR      | 4780 |
| 15 FR     | 4070 |
| 20 FR     | 3820 |
| 25 FR     | 3420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.